

GAUDÍ REF CAT 2	RECOMMENDED FOR Domestic & Contract use COMPOSITION 60%PP 35%PES 5%CO ABRASION RESISTANCE (END POINT) EN ISO 12947-2:1998 - 46000 PILLING RESISTANCE EN ISO 12945/2:2000; Modified martindale method (2000 and 7000 cycles) (Scale from 1 worst to 5 best): 4-5 FIRE TEST BS 5852 Source 1 (optional) EN 1021- part 2:2006 (optional) CAL TB 117:2013 California - AB-2998 NFPA 260:2013 BS 7176 Low Hazard (optional) UNI 9175 Clase 3IM (optional)	LIGHT FASTNESS EN ISO 105-B02:1998 & EN ISO 105 B02/ A01:2002 COLOUR DEGRADATION On blue scale (Scale from 1 worst to 8 best): 6-7 COLOUR FASTNESS TO RUBBING (DRY AND WET) EN ISO 105-X12:2002 (Scale from 1 worst to 5 best): 4-5 WASHING CONDITIONS 	 Example: LIGHT GREY – TG02
 LIGHT GREY – TG02	 GREY– TG12	 PALE PINK – TG29	 PURPLE – TG48
 BLACK – TG53	 ORANGE – TG60		